

FURUNO FS-1503EM

- NEW - Low Cost/High Quality Truly Marineized HF Transceiver
- 100% Duty Cycle @ 150W
- INCLUDED: Remote Control Capability and Integrated Narrowband Filter at ALL AT NO ADDITIONAL COST - Competitive Advantage!
- INCLUDED: Fully Automatic, High Quality, Computerized Antenna Coupler with 10 Meter Control Cable ALL AT NO ADDITIONAL COST - Competitive Advantage!
- Integrated Fan within Isolated Cavity Keeps Humid Cooling Air Away From Sensitive Electronics
- Dedicated RF Gain Control Rotary Knob - Competitive Advantage!
- Easy Front Panel "Clarifier" Control via Rotary Knob - Competitive Advantage!
- Fully Compatible with SCS Pactor IIe and SCS Pactor II PRO HF Modems
- 100% "Airmail" PC Software Compatibility with Radio Control (Requires SCS PACTOR IIpro)
- Single Rear Panel, Positive Locking Connection to Remote SCS Modem (w/Modem Supply Power Provided)
- FREE - Open Transmitter for Full Transmit From 1.8 - 27.5MHz (Ham license require when TX is used in non-marine bands)
- Receiver open for .1-30MHz
- Direct Keypad or Rotary Knob Channel Entry
- 20% Smaller "Foot Print" Than Leading Competitor - Competitive Advantage!
- All ITU and USA Channels
- Programmed In Memory
- Multiple Scan/Sweep Modes and Included 2182 Watch Alarm



INTRODUCING THE FURUNO FS-1503EM 100% SAIL-MAIL/EMAIL READY, MARINE SSB RADIO W/INCLUDED AUTOMATIC ANTENNA COUPLER

- Ruggedized Aluminum Chassis With Unique "Low Noise" Compartmentalized RF Section Design
- 199 User Channels and Alphanumeric Channel Name Capabilities
- 12VDC Operation with 2 Year Warranty

The Furuno FS-1503EM is the latest generation commercial SSB product. This "EM" version of the FS-1503 provides all of the necessary components and options to allow a single point direct connection to the latest generation SCS PactorII™ Modems used for the "Sailmail™" HF Email Service Worldwide Network.

The FS-1503 is part of Furuno's extensive commercial HF Radio line that has won the prestigious NMEA Award for SSB/Satellite "Global Maritime Distress and Safety Communications" for the past two years in a row.

The powerful 150 Wpwp transmitter provides reliable long distance communication. A large cooling fan with the solid aluminum chassis allows continuous transmission at full power for demanding RTTY (radio-teletype) and email modems. Fully Automatic Tuning is a standard feature and the wide-band receiver coverage allows you to monitor amateur bands, short-wave broadcast, aviation wx. The FS-1503EM also has full Marine HF Weatherfax Signal Receive capability.

Specifications subject to change without notice.



www.Furuno.com